HARDOX® 400 PLATE

2018-01-12

The table shows available dimensions in mm for direct order including the maximum length.

Some restrictions, contact your local sales representative for more information

Some restrictions on dimensions and minimum quantities, contact your sales representative for more information

Outside the range of dimensions

Only 1650 mm width, mill edges -0/+70 mm. Other dimensions must be approved by product manager Hardox®. For thermally cut edges, contact local sales force

Minimum lenght: 2000 mm

Minimum quantities:

Thickness:	Min. position weight:
4.0-60.0	2.5 tons
60.1-100.0	3.5 tons
100.1-120.0	4.0 tons
120.1-	5.0 tons

Width	1000-	1351-	1501-	1650	1601-	1701-	1801-	1901-	2001-	2101-	2201-	2301-	2401-	2501-	2601-	2701-	2801-	2901-	3001-	3101-	3201-	3301-
Thickness	1350	1500	1600		1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3350
3.2 - 3.9																						
4.0 - 4.7																						
4.8 - 5.7																						
5.8 - 6.0																						
6.1 - 6.7																						
6.8 - 7.7																						
7.8 - 8.7																						
8.8 - 10.0																						
10.1 - 25.0																						
25.1 - 26.0																						14600
26.1 - 27.0																					14200	14000
27.1 - 28.0																				14200	13700	13500
28.1 - 29.0																			14100	13700	13300	13100
29.1 - 30.0																		14100	13600	13200	12800	12600
30.1 - 31.0																	14100	13600	13200	12800	12400	12200
31.1 - 32.0				Maximum length 14630 mm												14200	13700	13200	12800	12400	12000	11800
32.1 - 33.0	14200														14200	13700	13300	12800	12400	12000	11600	11500
33.1 - 34.0	13800													14400	13800	13300	12900	12400	12000	11700	11300	11100
34.1 - 35.0	13400												14500	13900	13400	12900	12500	12100	11700	11300	11000	10800
35.1 - 36.0	13100												14100	13600	13100	12600	12200	11700	11400	11000	10700	10500
36.1 - 37.0	12700											14300	13700	13200	12700	12200	11800	11400	11100	10700	10400	10200
37.1 - 38.0	12400										14500	13900	13400	12800	12400	11900	11500	11100	10800	10400	10100	10000
38.1 - 39.0	12000										14200	13600	13000	12500	12000	11600	11200	10800	10500	10200	9800	9700
39.1 - 40.0	11700									14400	13800	13200	12700	12200	11700	11300	10900	10600	10200	9900	9600	9500
40.1 - 45.0	10400							14100	13400	12800	12300	11700	11300	10800	10400	10100	9700	9400	9100	8800	8500	8400
45.1 - 50.0	9400					14100	13400	12700	12100	11500	11000	10600	10100	9700	9400	9000	8700	8400	8200	7900	7700	7600
50.1 - 55.0	9000		14400		13600	12800	12100	11500	11000	10500	10000	9600	9200	9000	9000	9000	7900	7700	7400	7200	7000	6900
55.1 - 60.0	8600	14100	13200		12400	11700	11100	10600	10100	9600	9200	9000	9000	8900	8600	8300	7300	7000	6800	6600	6400	6300
60.1 - 65.0	7900	13000	11200		11200	10800	10300	9700	9300	9000	9000	8900	8500	8200	7900	7600	6700	6500	6300			
65.1 - 70.0	7300	12100	11200	12100	10700	10100	9500	9000	9000	8900	8600	8200	7900	7600	7300	7000	6200					
70.1 - 75.0	6800	11300	10600	11300	10000	9400	9000	9000	8700	8300	7900	7600	7300	7000	6800	6500						
75.1 - 80.0	6300	10600	9900	10600	9400	9000	8900	8500	8100	7700	7400	7100	6800	6600	6300	6100						
80.1 - 85.0	5900	9900	9300	10000	8800	8800	8400	8000	7600	7300	6900	6700	6400	6100	5900	5700						
85.1 - 90.0	5500	9400	9000	9400	8300	8300	7900	7500	7200	6800	6500	6300	6000	5800	5500	5300						
90.1 - 95.0	5200	9000	8800	8900	7900	7900	7400	7100	6700	6400	6200	5900	5700	5400	5200	5000						
95.1 - 100.0	4900	8900	8300	8500	7500	7400	7000	6700	6400	6100	5800	5600	5300	5100	4900	4800						
100.1 - 105.0	4700	8400	7900	8000	7100	7100	6700	6400	6100	5800	5500	5300	5100	4900	4700	4500						
105.1 - 110.0	4400	8000	7500	7700	6800	6700	6400	6000	5800	5500	5200	5000	4800	4600	4400	4300						
110.1 - 115.0	4200	7600	7200	7300	6500	6400	6100	5800	5500	5200	5000	4800	4600	4400	4200	4100						
115.1 - 120.0	4000	7300	6800	7000	6200	6100	5800	5500	5200	5000	4800	4600	4400	4200	4000	3900						
120.1 - 125.0	3800	7000	6600	6800	5900	5800	5500	5200	5000	4800	4500	4400	4200	4000	3800	3700						
125.1 - 130.0	3700	6700	6300	6500	5700	5600	5300	5000	4800	4600	4400	4200	4000	3800	3700							
130.1 - 135.0																						
135.1 - 140.0																						

HARDOX® 400 SHEET

The table shows available dimensions mm for direct order including maximum length.

Cut lengths with mill edges, black

Some restrictions, please contact product manager or Tech support, techsupport@ssab.com

Outside the range of dimensions

Min. length 1500 mm

Min. bundle weight 2 tons

Width	950-	1001-	1201-	1251-	1301-	1501-	1526-	1551-	1576-	1601-	1626-
Thickness	1000	1200	1250	1300	1500	1525	1550	1575	1600	1625	1650
2.00 - 2.49											
2.50 - 2.99											
3.00 - 3.19											
3.20 - 3.49											
3.50 - 3.99											
4.00 - 4.49											
4.50 - 4.79											
4.80 - 4.99											
5.00 - 5.99					Maximum length 16 000 mm						
6.00 - 6.40											
6.41 - 6.50											
6.51 - 6.99											
7.00 - 8.00											
8.10 - 10.0											
10.1 - 25.0											
25.1 - 26.0											
26.1 - 27.0											

Min position weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width.

Delivery weight accuracy +/- 10 %, at least -2 tons / + 3 tons.